

# Package: Rilostat (via r-universe)

September 3, 2024

**Type** Package

**Title** ILO Open Data via Ilostat Bulk Download Facility

**Date** 2024-09-03

**Version** 2.2.0

**Encoding** UTF-8

**Maintainer** David Bescond <bescond@ilo.org>

**Description** Tools to download data from the ilostat database  
<<https://ilostat.ilo.org>> together with search and manipulation  
utilities.

**License** BSD\_2\_clause + file LICENSE

**Depends** R (>= 4.1.0)

**Imports** plyr, dplyr (>= 1.1.2), stringr (>= 1.5.0), readr (>= 2.1.4),  
tibble (>= 3.2.1), haven, data.table

**Suggests** shiny

**LazyData** true

**URL** <https://ilostat.github.io/Rilostat/>

**BugReports** <https://github.com/ilostat/Rilostat/issues>

**RoxygenNote** 7.3.2

**Repository** <https://ilostat.r-universe.dev>

**RemoteUrl** <https://github.com/ilostat/rilostat>

**RemoteRef** HEAD

**RemoteSha** 0bc75f01ac32486639820dd637d2e64f78322cd9

## Contents

clean_ilstat_cache . . . . .	2
dataexplorer . . . . .	3
distribution_ilstat . . . . .	4
get_ilstat . . . . .	5

get_ilstat_dic . . . . .	8
get_ilstat_toc . . . . .	9
label_ilstat . . . . .	11
Rilostat . . . . .	13

<b>Index</b>	<b>14</b>
--------------	-----------

---

clean_ilstat_cache	<i>Clean Iloststat Cache</i>
--------------------	------------------------------

---

### Description

Deletes all cache files from the your ilostat cache directory. See [get\\_ilstat](#) for more on cache.

### Usage

```
clean_ilstat_cache(
  cache_dir = getOption("ilstat_cache_dir", file.path(tempdir(), "ilstat")),
  cache_update = getOption("ilstat_cache_update", FALSE),
  quiet = getOption("ilstat_quiet", FALSE)
)
```

### Arguments

cache_dir	A character, path to a cache directory. The directory has to exist. The NULL (default) uses and creates 'ilstat' directory in the temporary directory from <a href="#">tempdir</a> . The directory can also be set with option <code>ilstat_cache_dir</code> ,
cache_update	a logical whether to delete only out of date cache files. Useful when <code>cache_dir</code> is set as keep only update datasets. Can be set also with options( <code>ilstat_update = TRUE</code> ). Default is FALSE.
quiet	a logical, if TRUE , don't return message from processing, FALSE (default). Can be set also with options( <code>ilstat_quiet = TRUE</code> ),

### Author(s)

David Bescond <bescond@ilo.org>

### References

See citation("Rilostat") ilostat bulk download facility user guidelines [https://webapps.ilo.org/ilstat-files/Documents/ILOSTAT\\_BulkDownload\\_Guidelines.pdf](https://webapps.ilo.org/ilstat-files/Documents/ILOSTAT_BulkDownload_Guidelines.pdf)

### Examples

```
## Not run:
clean_ilstat_cache()

## End(Not run)
```

---

dataexplorer                      *Play with ilostat data explorer*

---

## Description

open ilostat data explorer app on your computer.

## Usage

```
dataexplorer(  
  port = getOption("shiny.port", 3838),  
  launch.browser = getOption("shiny.launch.browser", interactive()),  
  host = getOption("shiny.host", "127.0.0.1"),  
  display.mode = "normal"  
)
```

## Arguments

port	The TCP port that the application should listen on. If the 'port' is not specified, and the 'shiny.port' option is set (with 'options(shiny.port = XX)'), then that port will be used. Otherwise, use the 3838 port.
launch.browser	If true, the system's default web browser will be launched automatically after the app is started. Defaults to true in interactive sessions only. This value of this parameter can also be a function to call with the application's URL.
host	The IPv4 address that the application should listen on. Defaults to the 'shiny.host' option, if set, or "127.0.0.1" if not. See Details.
display.mode	The mode in which to display the application. If set to the value "showcase", shows application code and metadata from a DESCRIPTION file in the application directory alongside the application. If set to "normal", displays the application normally. Defaults to "auto", which displays the application in the mode given in its DESCRIPTION file, if any.

## Author(s)

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat")

## Examples

```
## Not run:  
  
require(shiny)  
  
dataexplorer()
```

```
## End(Not run)
```

---

distribution\_iloostat *Switch iloostat to distribution*

---

## Description

Get distribution for iloostat number of persons only.

## Usage

```
distribution_iloostat(x, var, .keep = FALSE)
```

## Arguments

x	dataset to transform into distribution.
var	String variable name use for the distribution default "no", could be "sex", "classif1", "classif2".
.keep	if true return only new column call distribution default FALSE.

## Details

this function use the max of the corresponding grouping so it is important to not filter any subset of the corresponding variable selected for the distribution at this level, ie. if you remove SEX\_T, the distribution by sex will only have SEX\_F or SEX\_M / max(SEX\_M, SEX\_F) \* 100, which is no longer a distribution.

In addition, distribution is only applicable for indicators with Number of persons (usually in thousands), So pls do not distribute ratios, earnings, hours of works, CPI, GDP etc ... no warning will prevent for that if doubts use distribution from get\_iloostat() instead of, warnings will help you.

## Value

a data\_frame. obs\_status will no longer be a number of persons but a percentage.

## Author(s)

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat") iloostat bulk download facility user guidelines [https://webapps.ilo.org/iloostat-files/Documents/ILOSTAT\\_BulkDownload\\_Guidelines.pdf](https://webapps.ilo.org/iloostat-files/Documents/ILOSTAT_BulkDownload_Guidelines.pdf)

**Examples**

```
## Not run:
dat <- get_ilocat("EMP_TEMP_SEX_STE_GEO_NB_A", cache = FALSE)
dat_dist <- distribution_ilocat(dat, "classif1")
dat_plus_dist <- mutate(dat, dist = distribution_ilocat(dat,"classif1", .keep=TRUE))
head(dat_dist)
clean_ilocat_cache()

## End(Not run)
```

get\_ilocat

*Read Ilocat Data***Description**

Download datasets from ilostat <https://ilostat.ilo.org> via bulk download facility <https://ilostat.ilo.org/data/bulk/>.

**Usage**

```
get_ilocat(
  id,
  segment = getOption("ilocat_segment", "indicator"),
  type = getOption("ilocat_type", "code"),
  lang = getOption("ilocat_lang", "en"),
  time_format = getOption("ilocat_time_format", "raw"),
  filters = getOption("ilocat_filter", "none"),
  fixed = getOption("ilocat_fixed", TRUE),
  detail = getOption("ilocat_detail", "full"),
  cache = getOption("ilocat_cache", TRUE),
  cache_update = getOption("ilocat_cache_update", TRUE),
  cache_dir = getOption("ilocat_cache_dir", NULL),
  cache_format = getOption("ilocat_cache_format", "rds"),
  back = getOption("ilocat_back", TRUE),
  cmd = getOption("ilocat_cmd", "none"),
  quiet = getOption("ilocat_quiet", FALSE)
)
```

**Arguments**

id	A code name for the dataset of interest. See <a href="#">get_ilocat_toc</a> or details for how to get code.
segment	A character, way to get datasets by: "indicator" (default) or "ref_area". Can be set also with options(ilocat_segment = 'ref_area'),
type	a character, type of variables, "code" (default), "label" or "both". Can be set also with options(ilocat_type = 'both'),

lang	a character, code for language. Available are "en" (default), "fr" and "es". Can be set also with options(ilstat_lang = 'fr'),
time_format	a string giving a type of the conversion of the time column from the ilstat format. "raw" (default) does not do conversion and return time as character (ie. '2017', '2017Q1', '2017M01'). A "date" converted to a <a href="#">Date</a> with a first date of the period. A "date_last" converted to a <a href="#">Date</a> with a last date of the period and "num" converted to a numeric. Can be set also with options(ilstat_time_format = 'date'),
filters	a list; "none" (default) to get a whole dataset or a named list of filters to get just part of the table. Names of list objects are ilstat variable codes and values are vectors of observation codes. filters detect on variables, so could be partial, ie. list(sex = 'T') is enough but equivalent to list(sex = 'SEX_T'). Additional options: <ul style="list-style-type: none"> <li>• timefrom : starting year of the return dataset,</li> <li>• timeto : ending year of the return dataset.</li> </ul>
fixed	a logical, if TRUE (default), filters arguments pattern is a string to be matched as is, Change to FALSE if more complex regex matching is needed.
detail	a character, 'full' (default), whether 'serieskeyonly', return only key, no data, no notes or dataonly return key and data, no notes or 'bestsourceonly' return best source only at the series key levels, see details. Can be set also with options(ilstat_detail = 'serieskeyonly'),
cache	a logical whether to do caching. Default is TRUE. Affects only queries from the ilstat bulk download facility. Can be set also with options(ilstat_cache = FALSE),
cache_update	a logical whether to update cache. Check cache update with last.update attribute store on the cache file name and the one from the table of contents. Can be set also with options(ilstat_cache_update = FALSE). Default is TRUE,
cache_dir	a path to a cache directory. The directory has to exist. The NULL (default) uses and creates 'ilstat' directory in the temporary directory from <a href="#">tempdir</a> . The directory can also be set with option ilstat_cache_dir,
cache_format	a character, format to store on the cache "rds" (default), but also "csv", "dta", "sav", "sas7bdat". useful for getting ilstat dataset directly on the cache_dir without R. Can be set also with options(ilstat_cache_format = 'dta'),
back	a logical, TRUE return dataframe on R or not FALSE, useful for just saving file in specific cache_format,
cmd	a character, R expression use for manipulate internal data frame dat object applied to each datasets retrieved If use, cache is set to FALSE. see examples.
quiet	a logical, if TRUE , don't return message from processing, FALSE (default). Can be set also with options(ilstat_quiet = TRUE),

### Value

a tibble. One column for each dimension in the data and the values column for numerical values, as well as the metadata columns. The time column for a time dimension.

## others

Data sets are downloaded from the iloostat bulk download facility. If only the table id is given, the whole table is downloaded from the bulk download facility.

The bulk download facility is the fastest method to download whole datasets. It is also often the only way as the sdmx API has limitation of maximum 300 000 records at the same time and whole datasets usually exceeds that.

By default datasets from the bulk download facility are cached as they are often rather large.

Cache files are stored in a temporary directory by default or in a named directory if `cache_dir` or option `iloostat_cache_dir` is defined. The cache can be emptied with [clean\\_iloostat\\_cache](#).

The id, a code, for the dataset can be searched with the [get\\_iloostat\\_toc](#) or from the [bulk download facility](<https://iloostat.ilo.org/data/bulk/>).

## Author(s)

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat") iloostat bulk download facility user guidelines <https://iloostat.ilo.org/data/bulk/>

## See Also

[get\\_iloostat\\_toc](#), [label\\_iloostat](#)

## Examples

```
## Not run:
##### get simple dataset
dat <- get_iloostat("UNE_2UNE_SEX_AGE_NB_A")
head(dat)
dat <- get_iloostat("NZL_Q", segment = "ref_area")
head(dat)

dir.create(file.path(tempdir(), "r_cache"))
dat <- get_iloostat("UNE_2UNE_SEX_AGE_NB_A",
                  cache_dir = file.path(tempdir(), "r_cache"))
head(dat)

clean_iloostat_cache(cache_dir = file.path(tempdir(), "r_cache"))

options(iloostat_update = TRUE)
dat <- get_iloostat("UNE_2UNE_SEX_AGE_NB_A")
head(dat)
options(iloostat_update = FALSE)
options(iloostat_cache_dir = file.path(tempdir(), "r_cache"))
dat <- get_iloostat("UNE_2UNE_SEX_AGE_NB_A")

clean_iloostat_cache()
```

```
##### get multiple datasets
dat <- get_ilstat(c("CPI_ACPI_COI_RT_M", 'CPI_ACPI_COI_RT_Q'), cache = FALSE)
head(dat)
toc <- get_ilstat_toc(search = 'CPI_')
head(toc)
dat <- get_ilstat(toc, cache = FALSE) #id as a tibble

##### get datasets with filters
dat <- get_ilstat(id = c("UNE_2UNE_SEX_AGE_NB_A", 'EMP_2EMP_SEX_AGE_NB_A'),
  filters = list( ref_area = "FRA",
    classif1 = "AGE_YTHADULT_YGE15",
    time = "2016",
    sex = c("T", 'SEX_F')), quiet = TRUE)
head(dat)
clean_ilstat_cache()

##### store in other format
dir.create(file.path(tempdir(), "ilstat"))

dat <- get_ilstat("UNE_2UNE_SEX_AGE_NB_A",
  cache_dir = file.path(tempdir(), "r_cache"), cache_format = 'csv')
dat <- get_ilstat("UNE_2UNE_SEX_AGE_NB_A",
  cache_dir = file.path(tempdir(), "r_cache"), cache_format = 'dta')

##### advanced manipulation

dat <- get_ilstat("UNE_2UNE_SEX_AGE_NB_A", cmd = "dat %>% count(ref_area)", quiet = TRUE)
label_ilstat(dat, code = 'ref_area')

clean_ilstat_cache()

## End(Not run)
```

---

get\_ilstat\_dic

*Read Ilost Dictionary*


---

## Description

Downloads one ilostat dictionary from ilostat <https://ilostat.ilo.org> via bulk download facility <https://ilostat.ilo.org/data/bulk/>.

## Usage

```
get_ilstat_dic(dic, lang = getOption("ilostat_lang", "en"))
```

## Arguments

dic	A character, dictionary for the variable to be downloaded,
lang	a character, code for language. Available are "en" (default), "fr" and "es". Can be set also with options(ilostat_lang = 'fr'),



## Details

For a given coded variable from ilostat <https://ilstat.ilo.org/>. The dictionaries link codes with human-readable labels. To translate codes to labels, use [label\\_ilstat](#).

## Value

tibble with two columns: code names and full names.

## Author(s)

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat") ilostat bulk download facility user guidelines [https://webapps.ilo.org/ilstat-files/WEB\\_bulk\\_download/ILOSTAT\\_BulkDownload\\_Guidelines.pdf](https://webapps.ilo.org/ilstat-files/WEB_bulk_download/ILOSTAT_BulkDownload_Guidelines.pdf) ilostat bulk download facility main page <https://ilstat.ilo.org/data/bulk/>

## See Also

[label\\_ilstat](#), [get\\_ilstat](#).

## Examples

```
## Not run:
tmp <- get_ilstat_dic("indicator")
head(tmp)
tmp <- get_ilstat_dic("classif1", lang = "fr")
head(tmp)

## End(Not run)
```

---

get\_ilstat\_toc

*Read Ilostat Table of Contents*

---

## Description

Download one table of contents from ilostat <https://ilstat.ilo.org> via bulk download facility <https://ilstat.ilo.org/data/bulk/>.

## Usage

```
get_ilstat_toc(
  segment = getOption("ilstat_segment", "indicator"),
  lang = getOption("ilstat_lang", "en"),
  search = getOption("ilstat_search", "none"),
  filters = getOption("ilstat_filter", "none"),
  fixed = getOption("ilstat_fixed", TRUE)
)
```

**Arguments**

segment	A character, way to get datasets by: "indicator" (default) or "ref_area", Can be set also with options(iloostat_segment = 'ref_area'),
lang	a character, code for language. Available are "en" (default), "fr" and "es". Can be set also with options(iloostat_lang = 'fr'),
search	a character vector, "none" (default), datasets with this pattern in the description will be returned, characters vector will be use as AND, Character with 'l' as OR, see example, options(iloostat_time_format = 'date'),
filters	a list; "none" (default) to get a whole toc or a named list of filters to get just part of the table. Names of list objects are iloostat toc variable codes and values are vectors of observation codes. filters detect on variables.
fixed	a logical, if TRUE (default), pattern is a string to be matched as is, Change to FALSE if more complex regex matching is needed.

**Details**

The TOC in English by indicator is downloaded from [https://webapps.ilo.org/iloostat-files/WEB\\_bulk\\_download/indicator/table\\_of\\_contents\\_en.csv](https://webapps.ilo.org/iloostat-files/WEB_bulk_download/indicator/table_of_contents_en.csv). The values in column 'id' should be used to download a selected dataset.

The TOC in English by ref\_area is downloaded from [https://webapps.ilo.org/iloostat-files/WEB\\_bulk\\_download/ref\\_area/table\\_of\\_contents\\_en.csv](https://webapps.ilo.org/iloostat-files/WEB_bulk_download/ref_area/table_of_contents_en.csv). The values in column 'id' should be used to download a selected dataset.

**Value**

A tibble with ten columns depending of the segment: indicator or ref\_area

- id : The codename of dataset of theme, will be used by the get\_iloostat and get\_iloostat\_raw functions,
- indicator or ref\_area : The indicator or ref\_area code of dataset,
- indicator.label or ref\_area.label : The indicator or ref\_area name of dataset,
- freq : The frequency code of dataset,
- freq.label : Is freq name of dataset,
- size : Size of the csv.gz files,
- data.start : First time period of the dataset,
- data.end : Last time period of the dataset,
- last.update : Last update of the dataset,
- ... : Others relevant information

**Author(s)**

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat") ilostat bulk download facility user guidelines [https://webapps.ilo.org/ilostat-files/WEB\\_bulk\\_download/ILOSTAT\\_BulkDownload\\_Guidelines.pdf](https://webapps.ilo.org/ilostat-files/WEB_bulk_download/ILOSTAT_BulkDownload_Guidelines.pdf)

## See Also

[get\\_ilstat](#).

## Examples

```
## Not run:
## default segment by indicator, default lang English
toc <- get_ilstat_toc()
head(toc)
toc <- get_ilstat_toc(segment = 'ref_area', lang = 'fr')
head(toc)
##
## search on toc
toc <- get_ilstat_toc(search = 'education')
head(toc)
toc <- get_ilstat_toc(lang = 'fr', search = 'éducation')
head(toc)
toc <- get_ilstat_toc(segment = 'ref_area', lang = 'fr', search = 'Albanie')
toc
toc <- get_ilstat_toc(segment = 'ref_area', lang = 'es', search = 'Trimestral')
head(toc)
##
## search multi on toc
toc <- get_ilstat_toc(segment = 'ref_area', lang = 'fr',
  search = 'Albanie|France', fixed = FALSE)
head(toc)
toc <- get_ilstat_toc(search = 'youth|adult', fixed = FALSE)
head(toc)
toc <- get_ilstat_toc(search = c('youth','adult'), fixed = FALSE)
head(toc)
##

## End(Not run)
```

---

label\_ilstat

*Switch Iloststat codes and labels*

---

## Description

Gets definitions/labels for ilostat codes from ilostat dictionaries.

## Usage

```
label_iloostat(  
  x,  
  dic = NULL,  
  code = NULL,  
  lang = getOption("iloostat_lang", "en")  
)
```

## Arguments

x	A character or a factor vector or a data_frame to labelled.
dic	A string (vector) naming iloostat dictionary or dictionaries. If NULL (default) dictionary names are taken from column names of the data_frame. A character or a factor vector or a data_frame to labelled,
code	a vector of names of the column for which code columns should be retained. Set to "all", keep all the code.
lang	a character, code for language. Available are "en" (default), "fr" and "es". Can be set also with options(iloostat_lang = 'fr'),

## Details

A character or a factor vector of codes returns a corresponding vector of definitions. label\_iloostat labels also data\_frames from `get_iloostat`. For vectors a dictionary "time" and "values" columns are returned as they were, so you can supply data\_frame from `get_iloostat` and get data\_frame with definitions instead of codes.

## Value

a vector or a data\_frame. The suffix ".label" is added to code column names.

## Author(s)

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat") iloostat bulk download facility user guidelines [https://webapps.ilo.org/iloostat-files/Documents/ILOSTAT\\_BulkDownload\\_Guidelines.pdf](https://webapps.ilo.org/iloostat-files/Documents/ILOSTAT_BulkDownload_Guidelines.pdf)

## Examples

```
## Not run:  
dat <- get_iloostat("UNE_2UNE_SEX_AGE_NB_A", cache = FALSE)  
dat_lab <- label_iloostat(dat)  
head(dat_lab)  
clean_iloostat_cache()  
  
## End(Not run)
```

---

Rilostat

*Get more Support*

---

## Description

On regular basis new tutorial and examples are building and available through this function.

## Details

brief description of the package

Package:	Rilostat
Type:	Package
Version:	See sessionInfo() or DESCRIPTION file
Date:	2020-2025
License:	BSD_2_clause + LICENSE
LazyLoad:	yes

R Tools for ilostat Open Data

## Author(s)

David Bescond <bescond@ilo.org>

## References

See citation("Rilostat")

ilostat bulk download facility user guidelines [https://webapps.ilo.org/ilostat-files/Documents/ILOSTAT\\_BulkDownload\\_Guidelines.pdf](https://webapps.ilo.org/ilostat-files/Documents/ILOSTAT_BulkDownload_Guidelines.pdf)

## Examples

```
## Not run:  
  
# check which documentation have been recently added:  
  
# help(Rilostat)  
  
# https://ilostat.github.io/Rilostat/  
  
## End(Not run)
```

# Index

- \* **database**

- get\_ilocstat\_dic, 8

- get\_ilocstat\_toc, 9

- \* **package**

- Rilostat, 13

- \* **utilities**

- get\_ilocstat\_dic, 8

- get\_ilocstat\_toc, 9

clean\_ilocstat\_cache, 2, 7

dataexplorer, 3

Date, 6

distribution\_ilocstat, 4

get\_ilocstat, 2, 5, 9, 11, 12

get\_ilocstat\_dic, 8

get\_ilocstat\_toc, 5, 7, 9

label\_ilocstat, 7, 9, 11

Rilostat, 13

tempdir, 2, 6